

6. ACCESSORIES

6.1 CANOPY

The canopy roof consists of a light-weight aluminum frame with a Sunbrella covering that is supported by four stainless steel posts. The roof has two zippered openings to make getting in and out of the boat easier. The zippers are functional from inside or outside the boat.



1. With the roof in its lowered position, install the Sunbrella covering onto the aluminium frame using the covering's Velcro attachments.
2. Install the covering as tautly as possible to prevent sagging.
3. Install the 6 support posts into the base brackets on the wooden coming.
4. Insert the quick release pins.
5. Install the roof frame onto the support posts, making sure that the stainless steel buttons click into the holes at the top of the support tubes.

Roof installation is easier with 2 people.

For storage and trailering, reverse the assembly process to remove the support tubes and lower the roof frame down onto the base brackets, thereby using the roof as a cover, and lower seats backs.



TRAILERING

It is not recommended to trailer the boat at highway speeds without a boat full cover to protect the roof material, since there is a possibility of it getting frayed by the wind.

6.2 SEATS AND STORAGE COMPARTMENTS

The Fantail Electric Boat has been designed to offer plenty of storage space under the front and back seats. You should use this storage space to store all your safety equipment, including the anchor and the fenders. Never forget to have your PDF's nearby.



SEATS

Always make sure that the seats are properly in place before departure.

6.3 LIFTING THE BOAT



When the boat is hoisted from the water, use the lifting eyes located in the bow (1) and rear (2) of the boat, or a sling for easy, damage free lifting.