

# 8. TRAILERING

For proper trailering, we strongly suggest that you use the special trailers made especially for CEBC's boats. These trailers have been designed to trailer the Quiétude 156 and the Fantail 217 for short and long distances. CEBC can not cover under warranty damage to a product caused by improper trailering.

## 8.1 HOW TO PROPERLY TRAILER YOUR BOAT



Carefully read the manufacturer instructions and warnings located in the front of your trailer.

Tie the front bow eye of the boat tightly to your trailer. The bow keel should slowly slide on the rubber cushion located at the bottom of the trailer. The rubber cushion protects the keel from the metal of the trailer. If the rubber cushion is worn out or missing, install a temporary soft interface like foam or a towel. Always make sure that the bow eye is hooked to the trailer tie down strap and that the security hook is also attached to the bow eye.



**POWDERED ABRASIVES ARE NOT RECOMMENDED**  
Never trailer your boat without the rubber cushion properly in place or with at least some kind of protective equipment installed on the front bottom of the trailer. Trailering without some kind of protective equipment or rubber cushion properly installed will damage the keel. CEBC doesn't warranty such damages.



Tie the rear of the boat to the trailer using tie down straps. Each rear bow eye should be tied down to one end of the trailer. Check that keel is centered on the trailer. Make sure that the motor shaft is properly attached to reduce the risk of loosening up parts due to road bumps and vibrations.